



# EVER-TITE<sup>®</sup> CRIMPRO SOLUTIONS

NEW PRODUCT

## PART C 4 HANDLE COUPLER

SIZE	ALUMINUM	PRESSURE
4"	340CAL4S	300 psi
6"	360CAL4S	150 psi



## ALUMINUM SLEEVES

- APG provides the most comprehensive line of aluminum sleeves in the industry.
- Manufactured from military grade seamless tube, eliminating potential weld issues when crimping.
  - Superior and consistent hose retention.
  - Eliminates the need for a slinky when traditional stainless steel bands are used.
- Provides a secure, non sparking, light weight, low cost alternative to stainless steel bands.
  - Eliminates buckles that catch on equipment or injure operators.
  - Non-Corrosive and rust resistant.
  - Aluminum Crimp Sleeves can be anodized in various colors.
- EVER-TITE<sup>®</sup> Crimp Sleeves are compatible with all EVER-TITE<sup>®</sup>, Tough-TITE<sup>®</sup>, U-TITE<sup>®</sup> Stainless Steel, Aluminum and Brass Cam and Coupling parts with Hose Shanks.

NEW DESIGN

## PART C

SIZE	ALUMINUM	PRESSURE
1-1/2"	315CAL	250 psi
2"	320CAL	250psi
3"	330CAL	125 psi
4"	340CAL	100 psi



NEW PRODUCT

## CRIMPRO NIPPLES

SIZE	STEEL PLATED	PRESSURE
1-1/2"	3TCNPG150	150 psi
2"	3TCNPG200	125 psi
3"	3TCNPG300	75 psi
4"	3TCNPG400	75 psi
6"	3TCNPG600	50 psi



## ALUMINUM MULTI-NOTCHED FERRULES

- Strengthen your industrial hose connection with APG/EVER-TITE crimp sleeves and notched ferrules. APG/EVER-TITE industrial hose couplings are the connection solution for demanding applications.
  - APG Ferrules provide a 360°interlock to fittings providing the best performance.
- Manufactured from military grade seamless tube, eliminating potential weld issues when crimping.
  - APG provides the most comprehensive line of aluminum ferrules in the industry.
- Provides a secure, non-sparking, light weight, low cost alternative to stainless steel bands.
  - EVER-TITE<sup>®</sup> Crimp ferrules are compatible with all EVER-TITE<sup>®</sup> Aluminum Cam and Groove and EVER-TITE<sup>®</sup> CRIMPRO Nipples .
- Contact APG for crimp specifications and procedures.

NEW DESIGN

## PART E

SIZE	ALUMINUM	PRESSURE
1-1/2"	315EAL	250 psi
2"	320EAL	250 psi
3"	330EAL	125 psi
4"	340EAL	100 psi
6"	360EALS	150 PSI



All products available with shoulder for multi-notched ferrules

HOUSTON, TEXAS

800-888-5223

800-444-3252

KNOXVILLE, TENNESSEE

800-382-8483

800-471-6586

SANTA FE SPRINGS, CALIFORNIA

800-500-4222

562-926-8870

## Crimp Sleeves and Ferrules

Size	Notched Ferrule	Multi-Notched Ferrule	Crimp Sleeve		Hose Dimensions (Inches)		Crimp Sleeve Dimensions (Inches)		
	304 Stainless Steel	Aluminum	304 Stainless Steel	Aluminum	OD min	OD max	Thickness	ID	Length
3/4"	-		307CRLASS	-	-	-	-	-	-
	307FRLASS		307CRSASS	307CRSAAL	1-1/32	1-1/8	0.065	1.15	1.5
	307FRLBSS		307CRSBSS	307CRSBAL	1-3/32	1-15/64	0.065	1.3	1.5
1"	310FRLASS		310CRSASS	310CRSAAL	1-29/64	1-35/64	.065	1.62	1.75
	310FRLBSS		310CRSBSS	310CRSBAL	1-9/16	1-11/16	.065	1.77	1.75
	-		-	310CRSCAL	1-21/32	1-25/32	.065	1.87	2
1-1/4"	-		312CRSASS	312CRSAAL	1-39/64	1-15/16	.065	2	2
	-		-	312CRSBAL	1-29/32	2-1/32	.065	2.1	2
1-1/2"	315FRLASS	315FRLAALN	315CRSASS	315CRSAAL	1-15/16	2-3/16	.083	2.334	2
	315FRLBSS		315CRSBSS	-	2-1/16	2-11/32	.065	2.37	2
	-		-	315CRSCAL	2-5/16	2-13/32	.083	2.45	2
2"	-		320CRSAASS	-	2-13/32	2-17/32	.083	2.56	2.25
	320FRLASS	320FRLAALN	320CRSASS	320CRSAAL	2-15/32	2-11/16	.083	2.709	2.25
	320FRLBSS	320FRLBALN	320CRSBSS	320CRSBAL	2-21/32	2-27/32	.120	2.885	2.25
	-	320FRLCALN	-	320CRSCAL	2-25/32	3	.120	3.085	2.25
2-1/2"	325FRLASS		325CRSASS	325CRSAAL	2-31/32	3-7/32	.12	3.26	2.75
	325FRLBSS		325CRSBSS	-	3-13/64	3-11/32	.12	3.385	2.75
	-		-	325CRSCAL	3-1/4	3-31/64	.12	3.51	3
3"	330FRLASS	330FRLAALN	330CRSASS	330CRSAAL	3-15/32	3-23/32	.12	3.76	3
	330FRLBSS	330FRLBALN	330CRSBSS	330CRSBAL	3-47/64	3-27/32	.12	3.885	3
	-	330FRLCALN	-	330CRSCAL	3-7/8	4	.12	4.01	3
	-		-	330CRSDAL	4	4-1/4	.12	4.375	3
4"	340FRLASS	340FRLAALN	340CRSASS	340CRSAAL	4-5/8	4-47/64	.12	4.76	3
	340FRLBSS	340FRLBALN	340CRSBSS	340CRSBAL	4-3/4	4-7/8	.12	5.01	3
5"	-		-	350CRSAAL	5-1/2	6	.12	5.4	4.45
6"	-		-	360CRSAAL	6-1/4	6-3/4	.155	6.75	5
	360FRLPS*	360FRLBALN	-	360CRSBAL	6-31/64	7-3/16	.175	7.25	5
8"	-		-	380CRSAAL4	8-5/16	8-15/16	.175	9.1	4
	-		-	380CRSAAL6	8-5/16	8-15/16	.175	9.1	6
	-		-	380CRSBAL4	8-15/16	9-1/2	.175	9.75	4
	-		-	380CRSBAL6	8-15/16	9-1/2	.175	9.75	6
	-		380CRSACS	-	8-5/16	8-15/16	0.125	9.1	4
	-		380CRSBSCS	-	8-15/16	9-1/2	0.125	9.75	4

\*ZINC PLATED

- APG/EVER-TITE® Notched Ferrules are compatible with ALL EVER-TITE® and Tough-TITE™ Stainless Steel Cam and Coupling Parts with Hose Shanks.

- 360FRLPS is compatible with the 4-handle part "C" (360CAL4S) and part "E" (360EALS) with round ferrule shoulder.

- APG/EVER-TITE® Crimp Sleeves are compatible with EVER-TITE®.

- APG/EVER-TITE® Crimp Sleeves are compatible with ALL EVER-TITE®, Tough-TITE™, and U-TITE® Stainless Steel, Aluminum and Brass Cam and Coupling Parts with Hose Shanks.

Note: APG/EVER-TITE coupling products ferrules and crimp sleeves should be used only in combination with one another. Different brands of these type products are not interchangeable in any combination.